

PRODUCT DATA



FAME™ - 2042 PAPER TO PLASTIC ADHESIVE **(TO BOND FILTER PAPER STAR WITH PLASTIC ENDS)**

INTRODUCTION



2042 SEALING ADHESIVE PASTE is an air drying solvent based thick pasty product comprising of Resins, Tackifiers and Rubber formulated to provide tough and strong bond between plastic (high impact polystyrene (HIPS), polystyrene, ABS etc.) components and filter paper. The product is specially designed to be used in the manufacture of Air Filters for Motorcycles to bond Filter Paper Star with Plastic components. The product when cured perfectly is air tight, water & oil proof.

APPLICATION

2042 SEALING ADHESIVE PASTE can be applied through dispenser or mechanized applicator, as under:-

- 1) Clean and dry the plastic component surface from dirt, dust, moisture, oil & grease.
- 2) Fill the plastic top/bottom with the predetermined quantity of compound by way of nozzle tipped can (ketch-up plastic bottle and place paper star appropriately therein.
- 3) Let the compound air dry and leave for 24 hours for seasoning before packing into cartons.
- 4) Wash the dispenser/applicator after every use by S.M.T. or solvent naphtha.

SPECIFICATIONS

COLOR

Yellow/White/Grey. Other colors on bulk orders.

ODOR

Solventy smell while wet, however dried film odorless.

CONSISTENCY/VISCOSITY

Free flowing liquid. Viscosity being 1.334 Kg./litre.

SOLID CONTENTS

54±1% depending upon the grades. (ASTM C-771)

APPLICATION

The product can be applied by Nozzle Tipped Can or Mechanical Dispenser.

HEALTH & SAFTY

The product is a hazardous substance within the meaning of current Dangerous Substance Regulations. Contains Toluene. Adequate ventilation must be ensured to avoid flash fire. Vapor build-up may cause headaches, dizziness or eye watering. Use respiratory protection if symptoms experienced and leave the area forthwith to ensure more fresh air. Contact with eyes, skin and clothing must be avoided. While using wear protective clothing.

If **breathing** difficulty experienced, move to fresh air. In case breathing problems persist, seek medical advice. In case of **eye** contact, flush thoroughly with water for 15 minutes. Get immediate medical attention. If **swallowed**, give 1 to 2 glass of water immediately & seek medical help. **DO NOT INDUCE VOMITING.**

STORAGE/SHELF LIFE

Up to 1 year if stored at 25 °C in air tight container

PACKING & DELIVERY

30, 75 & 150 Kg. Plastic Can/Wide Mouth Drum from ready stock.

Important Notice:

The information submitted in this leaflet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislations are observed.